

Greenhouse Sprayer

EPS



For larger commercial greenhouse growers

- Includes one MaxCharge™ electrostatic spraygun
- 220 volt, 3 hp electric motor
- Spray up to 40,000 sq. ft/hr
- Pull by hand or tow with a small vehicle
- Compatible with all conventional chemicals and fungicides



Technical Specifications

Nozzles	1
External air supply required	No
Electricity required	Yes
Standard hose length	150 ft. (45.7 m.)
Weight empty	230 lbs. (104.3 kg.)
Weight full	270 lbs. (122.5 kg.)
Shipping weight	350 lbs. (158.8 kg.)
Main tank capacity	5 gal. (18.9 l.)
Dimensions	31" H x 21" W x 36" L (0.8m. x 0.5m. x 0.9m.)
Air line pressure	50 PSI 3.5 kg./cm ²
Tank Pressure	12 – 15 PSI (0.8 – 1.1 kg./cm ²)
Flow rate	1 Nozzle 2.8 gal./hr. (10.6 L./hr.) 2 Nozzles 5.2 gal./hr. (19.7 L./hr.)
Drop size	40 microns
Spray range	15 to 20 ft. (4.6 m. - 6.1 m.)
Available options	250 ft. (76.2 m.) hose 2 nozzle spraygun

Call today for the best possible deal on a EPS sprayer for your operation.



Electrostatic Spraying Systems manufactures sprayers utilizing its patented MaxCharge™ technology. For more details please visit our website, www.maxcharge.com, or contact a representative at (706)769-0025.

Electrostatic Means Better Spray Coverage



Electrostatic
Spraying Systems

62 Morrison St. · Watkinsville, GA 30677-2749
Toll-Free: 800-213-0518 · Fax: 706-769-8072
www.maxcharge.com