

Greenhouse Sprayer

PTO215



Versatile and compact, multi-spraygun system that can be transported and powered by a small tractor

- Self-contained unit only needs a tractor to operate
- Quality heavy-duty construction
- 2 MaxCharge™ air-assisted electrostatic sprayguns
- Two removable 15 gallon tanks
- Category I & 2 lift class
- PTO powered, only 7 hp consumption
- Compatible with most conventional chemicals and fungicides



Technical Specifications

Nozzles per Spraygun	1 (2 optional)
3-point hitch	Yes (CAT 1 & 2)
Tanks	2 (15 gallons/56.8 L each)
Hose	2 (150 ft/45.7 meters each) Optional 250 ft/76.2 meters
Weight empty	≈ 500 lbs. (227 kg.)
Tank Pressure	12 – 15 PSI (0.84 – 1.05 kg./cm ²)
Flow rate	5 gal/hr (19 L/hr)
Drop size	40 microns
Spray distance	up to 20 ft (6.1 meters)



Electrostatic Spraying Systems manufactures sprayers utilizing its patented MaxCharge™ technology. For more details please visit our website, www.maxcharge.com, or contact a representative at (706)769-0025.

Call today for the best possible deal on a PTO215 sprayer for your operation.

Electrostatic Means Better Spray Coverage



Electrostatic
Spraying Systems

62 Morrison St. · Watkinsville, GA 30677-2749
Toll-Free: 800-213-0518 · Fax: 706-769-8072
www.maxcharge.com