

Greenhouse Sprayer



TRG

- Compatible with all conventional chemicals and fungicides
- Includes one MaxCharge™ electrostatic spraygun
- Tank agitator assures mixing of all chemicals
- For connection to an existing air supply
- Oversized, semi-pneumatic tires
- Stainless steel tank



Technical Specifications

Nozzle options	1, 2 or 3
External air supply required	Yes
Electricity required	No
Standard hose length	150 ft. (45.7 m.)
Weight empty	80 lbs. (36.3 kg.)
Weight full	132 lbs. (60 kg.)
Shipping weight	275 lbs. (124.7 kg.)
Main tank capacity	5 gal. (18.9 l.)
Dimensions	31" H x 21" W x 36" L (0.8m. x 0.5m. x 0.9m.)
Air volume required	1 Nozzle 6-8 CFM (0.17 - 0.23 m ³ /min.) 2 Nozzles 12-16 CFM (0.34 - 0.45 m ³ /min.) 3 Nozzles 18-24 CFM (0.51 - 0.68 m ³ /min.)
Air line pressure	65-90 PSI (4.6 - 6.3 kg./cm ²)
Tank Pressure	10 PSI (0.7 kg./cm ²)
Flow rates	1 Nozzle - 2-2.5 gal./hr. (7.6-9.5 l./hr.) 2 Nozzles - 4-4.5 gal./hr. (15-17 l./hr.) 3 Nozzles - 5.5-6 gal./hr. (20.8-22.7 l./hr.)
Drop size	40 microns
Spray range	10-15 ft. (3 - 4.6 m.)
Available options	250 ft. (76.2 m.) hose Aluminum trident spraygun



Electrostatic Spraying Systems manufactures sprayers utilizing its patented MaxCharge™ technology. For more details please visit our website, www.maxcharge.com, or contact a representative at (706)769-0025.

Call today for the best possible deal on a TRG sprayer for your operation.

Electrostatic Means Better Spray Coverage



**Electrostatic
Spraying Systems**

62 Morrison St. · Watkinsville, GA 30677-2749
Toll-Free: 800-213-0518 · Fax: 706-769-8072
www.maxcharge.com