

Orchard Sprayer

150SR



Supercharged

- 28-36 MaxCharge™ air-assisted electrostatic nozzles
- 48 in. (121.92 cm.) in width; 1300 lbs. (589.6 kg.) dry weight
- 100-150 gallon (379 -568 liter) poly tank
- Flow rate 0.89-1.71 gal/min (3.36-6.48L/min)
(Example: 4mph at 10 ft centers equals an application rate of 17-21 gal/acre (159-196 liters/hectare))
- Efficient and effective ultra low volume sprayer (40 micron droplet size) with minimum drift
- Supercharged blower means the spray goes higher and further
- Control Box with valve control and easy-to-see electrostatic charge indicators
- Compatible with most conventional chemicals and fungicides
- Excellent tree canopy and “under the leaf” coverage
- Compact easy 3-point hitch construction; PTO powered
- “Category 2/3” lift class; 45 horsepower (33.6 kW) tractor minimum required
- Adjustable spray bars



Electrostatic Spraying Systems manufactures sprayers utilizing its patented MaxCharge™ technology. For more details please visit our website, www.maxcharge.com, or contact a representative at (706)769-0025.



Call today for the best possible deal on a 150SR sprayer for your operation.

Electrostatic Means Better Spray Coverage



Electrostatic
Spraying Systems

62 Morrison St. · Watkinsville, GA 30677-2749
Toll-Free: 800-213-0518 · Fax: 706-769-8072
www.maxcharge.com